



2006 CATALOG

20 Series
Light Medium Duty Casters



Features

Heavily embossed, formed steel upper & lower cup.
Double row ball bearing swivel raceway construction.
Corrosion-resistant zinc plated finish.
Top locking brake system.

Applications

Stock carts, bakery racks, food service equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C2030S-**-SR	C2030R-**-SR	3"	1-1/4"	Soft Rubber	Nylon	4-1/4"	3"	125
C2030S-**-SRB	C2030R-**-SRB			Soft Rubber	Ball			125
C2030S-**-HR	C2030R-**-HR			Hard Rubber	Nylon			250
C2030S-**-HRB	C2030R-**-HRB			Hard Rubber	Ball			250
C2030S-**-HP	C2030R-**-HP			Heavy Plastic	Plain			250
C2030S-**-PY	C2030R-**-PY			Polyurethane	Ball			220
C2030S-**-INF	C2030R-**-INF			Infinity	Annular			220
C2030S-**-SS	C2030R-**-SS			Steel	Plain			250
C2035S-**-SR	C2035R-**-SR			3-1/2"	1-1/4"			Soft Rubber
C2035S-**-HR	C2035R-**-HR	Hard Rubber	Nylon			255		
C2035S-**-HP	C2035R-**-HP	Heavy Plastic	Nylon			255		
C2035S-**-PY	C2035R-**-PY	Polyurethane	Ball			260		
C2035S-**-INF	C2035R-**-INF	Infinity	Annular			220		
C2035S-**-RAL	C2035R-**-RAL	Rubber/Aluminum	Annular			220		
C2040S-**-SR	C2040R-**-SR	4"	1-1/4"			Soft Rubber	Nylon	5-1/8"
C2040S-**-SRB	C2040R-**-SRB			Soft Rubber	Ball	165		
C2040S-**-HR	C2040R-**-HR			Hard Rubber	Nylon	255		
C2040S-**-HRB	C2040R-**-HRB			Hard Rubber	Ball	255		
C2040S-**-HP	C2040R-**-HP			Plastic	Plain	265		
C2040S-**-PY	C2040R-**-PY			Polyurethane	Ball	265		
C2040S-**-INF	C2040R-**-INF			Infinity	Annular	240		
C2040S-**-SS	C2040R-**-SS			Steel	Plain	300		
C2040S-**-HT	C2040R-**-HT			High Temp	Steel	265		
C2050S-**-SR	C2050R-**-SR	5"	1-1/4"	Soft Rubber	Nylon	6-5/32"	4	175
C2050S-**-SRB	C2050R-**-SRB			Soft Rubber	Ball			175
C2050S-**-HR	C2050R-**-HR			Hard Rubber	Nylon			260
C2050S-**-HRB	C2050R-**-HRB			Hard Rubber	Ball			260
C2050S-**-HP	C2050R-**-HP			Plastic	Plain			300
C2050S-**-PY	C2050R-**-PY			Polyurethane	Ball			250
C2050S-**-INF	C2050R-**-INF			Infinity	Annular			250
C2050S-**-PH	C2050R-**-PH			Phenolic	Steel			300
FASTENING TYPE				FASTENING CODE				SPECIFICATIONS
Top Plate		A1	Overall Size		2-3/8 X 3-5/8"			
			Bolt Hole Spacing		1-3/4 X 2-11/16 to 2-15/16"			
			Attaching Bolt Size		5-16"			
Threaded Stem		A2	Overall Size		3-1/8 X 4-1/8"			
			Bolt Hole Spacing		1-3/4 X 2-15/16 to 2-3/8 X 3-3/8"			
			Attaching Bolt Size		3/8"			
Grip Ring Stem		A3	Overall Size		3-15/16 X 4-1/2"			
			Bolt Hole Spacing		2-5/8 X 3 to 3-5/8"			
			Attaching Bolt Size		3/8"			
			Bolt Hole Spacing		2-5/8 X 3 to 3-5/8"			
Threaded Stem		B1	1/2-13 X 1					
		B2	1/2-13 X 1-1/2"					
		B3	1/2-13 X 2-1/2" (Can be used with expanding applicator)					
		B4	5/8-11 X 1-1/4"					
Grip Ring Stem		D1	7/16 X 1-1/2"					
Octagon Stem		F1	27/32 X 2-7/16" with 1/4" cross drilled holes located 1/2, 1-1/8 & 1-3/4" from the top of raceway					
Accessories Code								
TB		Top Lock Brake						
TG		Thread Guard (Only on Casters with HRB & SRB wheels)						
STS		Stainless Steel Yoke						



8705 Tamarack Ave., Sun Valley, Ca. 91352
Toll Free (877) 252-0878---Phone (818) 252-0878---Fax (818) 252-0978