



2006 CATALOG

**21 Series  
Light Medium Duty Casters**



**Features**

Heavily embossed, formed steel upper & lower cup.  
 Double row ball bearing swivel raceway construction.  
 Dust cover helps protect swivel bearings.  
 Corrosion-resistant zinc plated finish  
 Top locking brake system.

**Applications**

Stock carts, bakery racks, food service equipment, sound & music equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C2125S-**-SR	C2125R-**-SR	2-1/2"	1-1/4"	Soft Rubber	Nylon	3-5/8"	2-3/4"	140
C2125S-**-HR	C2125R-**-HR			Hard Rubber	Nylon			210
C2125S-**-HP	C2125R-**-HP			Heavy Plastic	Plain			210
C2125S-**-PY	C2125R-**-PY			Polyurethane	Ball			210
C2130S-**-SR	C2130R-**-SR	3"	1-1/4"	Soft Rubber	Nylon	4-1/4"	2-3/4"	125
C2130S-**-SRB	C2130R-**-SRB			Soft Rubber	Ball			125
C2130S-**-HR	C2130R-**-HR			Hard Rubber	Nylon			250
C2130S-**-HRB	C2130R-**-HRB			Hard Rubber	Ball			250
C2130S-**-HP	C2130R-**-HP			Heavy Plastic	Plain			250
C2130S-**-PY	C2130R-**-PY			Polyurethane	Ball			220
C2130S-**-INF	C2130R-**-INF			Infinity	Annular			220
C2130S-**-SS	C2130R-**-SS			Steel	Plain			250
C2135S-**-SR	C2135R-**-SR	3-1/2"	1-1/4"	Soft Rubber	Nylon	4-11/16"	3-1/16"	130
C2135S-**-HR	C2135R-**-HR			Hard Rubber	Nylon			255
C2135S-**-HP	C2135R-**-HP			Heavy Plastic	Plain			255
C2135S-**-PY	C2135R-**-PY			Polyurethane	Ball			260
C2135S-**-INF	C2135R-**-INF			Infinity	Annular			230
C2135S-**-RAL	C2135R-**-RAL			Rubber/Aluminum	Annular			220
C2140S-**-SR	C2140R-**-SR	4"	1-1/4"	Soft Rubber	Nylon	5-1/8"	3-5/16"	165
C2140S-**-SRB	C2140R-**-SRB			Soft Rubber	Ball			165
C2140S-**-HR	C2140R-**-HR			Hard Rubber	Nylon			255
C2140S-**-HRB	C2140R-**-HRB			Hard Rubber	Ball			255
C2140S-**-HP	C2140R-**-HP			Heavy Plastic	Plain			265
C2140S-**-PY	C2140R-**-PY			Polyurethane	Ball			265
C2140S-**-INF	C2140R-**-INF			Infinity	Annular			250
C2140S-**-SS	C2140R-**-SS			Steel	Plain			300
C2140S-**-HT	C2140R-**-HT			High Temp	Plain			265
C2150S-**-SR	C2150R-**-SR	5"	1-1/4"	Soft Rubber	Nylon	6-7/32"	4"	175
C2150S-**-SRB	C2150R-**-SRB			Soft Rubber	Ball			175
C2150S-**-HR	C2150R-**-HR			Hard Rubber	Nylon			260
C2150S-**-HRB	C2150R-**-HRB			Hard Rubber	Ball			260
C2150S-**-HP	C2150R-**-HP			Heavy Plastic	Plain			300
C2150S-**-PY	C2150R-**-PY			Polyurethane	Ball			250
C2150S-**-INF	C2150R-**-INF			Infinity	Annular			250
C2150S-**-PH	C2150R-**-PH			Phenolic	Steel			300

FASTENING TYPE	FASTENING CODE	SPECIFICATIONS	
Top Plate	A1	Overall Size	2-3/8 X 3-5/8"
		Bolt Hole Spacing	1-3/4 X 2-11/16 to 2-15/16"
		Attaching Bolt Size	5-16"
	A2	Overall Size	3-1/8 X 4-1/8"
		Bolt Hole Spacing	1-3/4 X 2-15/16 to 2-3/8 X 3-3/8"
		Attaching Bolt Size	3/8"
	A3	Overall Size	3-15/16 X 4-1/2"
		Bolt Hole Spacing	2-5/8 X 3 to 3 X 3-5/8"
		Attaching Bolt Size	3/8"
Threaded Stem	B2	1/2-13 X 1-1/2"	
	B3	1/2-13 X 2-1/2" ( Can be used with expanding applicator)	
Accessories Code			
TB	Top Lock Brake		
TG	Thread Guard ( Only on Casters with HRB & SRB wheels)		
TLB	Total Lock Brake (Locks the swivel raceway and the wheel) Only available in 3-1/2, 4 or 5"		



8705 Tamarack Ave., Sun Valley, Ca. 91352  
Toll Free (877) 252-0878---Phone (818) 252-0878---Fax (818) 252-0978