



2006 CATALOG

30 Series Light Duty Casters



Features

High Durability Design.
Double row ball bearing swivel raceway construction.
Corrosion-resistant zinc plated finish.
Raceway and yoke hardened for extra strength.
Top locking brake system.

Applications

Interior furniture, office chairs, show cases etc..

CASTER PART #	WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C3020-**-SR	2"	13/16"	Soft Rubber	Nylon	2-5/8"	1-13/16"	66
C3020-**-HR			Hard Rubber	Nylon			77
C3020-**-PY			Polyurethane	Plain			66
C3020-**-INF			Infinity	Steel			66
C3025-**-SR	2-1/2"	13/16"	Soft Rubber	Nylon	3-1/8"	2-1/16"	77
C3025-**-HR			Hard Rubber	Nylon			99
C3030-**-SR	3"	13/16"	Soft Rubber	Nylon	3-5/8"	2-3/8"	99
C3030-**-HR			Hard Rubber	Nylon			110
C3030-**-PY			Polyurethane	Plain			100
C3030-**-INF			Infinity	Steel			100
FASTENING TYPE	FASTENING CODE			SPECIFICATIONS			
Top Plate	A1			Overall Size	1-1/4 X 2-1/16"		
				Bolt Hole Spacing	13/16 X 1-9/16"		
				Attaching Bolt Size	3/16"		
Grip Ring Stem	12			7/16 X 1-7/16"			
Threaded Stem	24			3/8-16 X 1-1/4"			

Side locking brakes are available, Add "-BRK" to the part number

80 Series

Business Machine Casters



Features

Double row ball bearing swivel raceway construction.
Corrosion-resistant zinc plated finish.
Provides floor protection and excellent mobility
Low profile design.

Applications

Pianos and other heavy equipment.

CASTER PART #	WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C8020S-A2-HP	2"	1-11/16"	Heavy Duty Plastic	Plain	2-13/16"	1-7/8"	400
C8022S-**-SR	2"	13/16" (2 Wheels)	Soft Rubber	Nylon	2-13/16"	1-7/8"	160
C8022S-**-HR			Hard Rubber	Nylon			200
C8030S-A3-PH	3"	1-13/16"	Phenolic	Roller	4-1/16"	2-5/16"	600
C8030S-A3-HP			Heavy Duty Plastic	Plain			600
C8030S-A3-NGF			Nylon Glass-Filled	Roller			600
TYPE	CODE	SPECIFICATIONS			USE WITH PART NUMBERS		
Top plate	A1	Overall	1-7/8 X 2-9/16"		C8022S		
		Hole Spacing	15/16 X 2-1/8"				
		Attaching Bolt Size	1/4"				
Top plate	A2	Overall	2-3/4 X 3-3/4"		C8020S, C8022S		
		Hole Spacing	1-3/4 X 2-7/8"				
		Attaching Bolt Size	5/16"				
Top plate	A3	Overall	3-1/8 X 4-1/8"		C8030S		
		Hole Spacing	2-3/8 X 3-23/64"				
		Attaching Bolt Size	5/16"				
Grip Ring	12	7/16 X 1-1/2"			C8022S		
Threaded Stem	21	1/2-13 X 1-1/2"			C8022S		



8705 Tamarack Ave., Sun Valley, Ca. 91352
Toll Free (877) 252-0878---Phone (818) 252-0878---Fax (818) 252-0978