



2006 CATALOG

**40 Series
Medium Heavy Duty Casters**



Features

Cold forged top plate & base.
 Double row ball bearing swivel raceway construction.
 Hardened Raceways.
 Zerk fitting on swivel raceway for lubrication.
 Legs are formed and welded to yoke base for strength.

Applications

Excellent for medium heavy duty platform carts, food service equipment and large stock carts, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C4040S-**-RC	C4040R-**-RC	4	2	Rubber/Cast Iron	Roller	5-5/8"	3-3/16"	350
C4040S-**-PC	C4040R-**-PC			Poly/Cast Iron				700
C4040S-**-PU	C4040R-**-PU			Poly/Polyolefin				500
C4040S-**-HP	C4040R-**-HP			Heavy Plastic				500
C4040S-**-PH	C4040R-**-PH			Phenolic				700
C4040S-**-SS	C4040R-**-SS			Cast Iron				700
C4040S-**-VG	C4040R-**-VG			V-Groove				700
C4040S-**-TR	C4040R-**-TR			Thermal Rubber				350
C4050S-**-RC	C4050R-**-RC			Rubber/Cast Iron				375
C4050S-**-PC	C4050R-**-PC	Poly/Cast Iron	800					
C4050S-**-PU	C4050R-**-PU	Poly/Polyolefin	800					
C4050S-**-HP	C4050R-**-HP	Heavy Plastic	650					
C4050S-**-PH	C4050R-**-PH	Phenolic	800					
C4050S-**-SS	C4050R-**-SS	Cast Iron	800					
C4050S-**-VG	C4050R-**-VG	V-Groove	800					
C4050S-**-TR	C4050R-**-TR	Thermal Rubber	375					
C4060S-**-RC	C4060R-**-RC	Rubber/Cast Iron	450					
C4060S-**-PC	C4060R-**-PC	Poly/Cast Iron	800					
C4060S-**-PU	C4060R-**-PU	Poly/Polyolefin	800					
C4060S-**-HP	C4060R-**-HP	Heavy Plastic	700					
C4060S-**-PH	C4060R-**-PH	Phenolic	800					
C4060S-**-SS	C4060R-**-SS	Cast Iron	800					
C4060S-**-VG	C4060R-**-VG	V-Groove	800					
C4060S-**-TR	C4060R-**-TR	Thermal Rubber	450					
C4080S-**-RC	C4080R-**-RC	Rubber/Cast Iron	500					
C4080S-**-PC	C4080R-**-PC	Poly/Cast Iron	900					
C4080S-**-PU	C4080R-**-PU	Poly/Polyolefin	900					
C4080S-**-HP	C4080R-**-HP	Heavy Plastic	800					
C4080S-**-PH	C4080R-**-PH	Phenolic	900					
C4080S-**-SS	C4080R-**-SS	Cast Iron	900					
C4080S-**-VG	C4080R-**-VG	V-Groove	900					
C4080S-**-TR	C4080R-**-TR	Thermal Rubber	500					

FASTENING TYPE		SPECIFICATIONS	
Top Plate	A1	Overall Size	4 X 4-1/2"
		Bolt Hole Spacing	2-5/8 X 3-5/8 TO 3 X 3"
		Attaching Bolt Size	3/8"
	A2	Overall Size	4-1/2 X 6-1/4"
Bolt Hole Spacing		2-7/16 X 4-15/16 to 3-3/8 X 5-1/4"	
Attaching Bolt Size		1/2"	
Accessories Code			
	TB	Top Locking Brake	
	SWL	4-Position Swivel Lock	
	ZA	Zerk Axle	
	STS	Stainless Steel	



8705 Tamarack Ave., Sun Valley, Ca. 91352
Toll Free (877) 252-0878---Phone (818) 252-0878---Fax (818) 252-0978