



2006 CATALOG

42 Series Heavy Duty Casters



Features

Cold Forged top plate and base.
Double row ball bearing swivel raceway construction for extra strength.
Corrosion-resistant zinc plated finish.
Raceway and yoke hardened for extra strength.
3/4" Diameter king pin.

Applications

Excellent for cargo containers, heavy duty platform trucks, food handling equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C4260S-A1-RC	C4260R-A1-RC	6"	2-1/2"	Rubber-Cast Iron	Roller	7-1/2"	4-7/16"	500
C4260S-A1-PC	C4260R-A1-PC			Ploy-Cast Iron				1500
C4260S-A1-PH	C4260R-A1-PH			Phenolic				1500
C4260S-A1-SS	C4260R-A1-SS			Steel				1500
C4280S-A1-RC	C4280R-A1-RC	8"	2-1/2"	Rubber-Cast Iron	Roller	9-1/2"	6"	600
C4280S-A1-PC	C4280R-A1-PC			Poly-Cast Iron				1600
C4280S-A1-PH	C4280R-A1-PH			Phenolic				1600
C4280S-A1-SS	C4280R-A1-SS			Steel				1600
C4210S-A1-RC	C4210R-A1-RC	10"	2-1/2"	Rubber-Cast Iron	Roller	11-1/2"	7-19/32"	800
C4210S-A1-PC	C4210R-A1-PC			Poly-Cast Iron				2200
C4210S-A1-PH	C4210R-A1-PH			Phenolic				2200
C4210S-A1-SS	C4210R-A1-SS			Steel				2200
FASTENING TYPE		SPECIFICATIONS						
Top Plate		Overall Size			4-1/2 X 6-1/4"			
		Bolt Hole Spacing			2-7/16 X 4-15/16 to 3-3/8 X 5-1/4"			
		Attaching Bolt Size			1/2"			

45 Series Pneumatic Casters



Features

Cold Forged top plate and base.
Double row ball bearing swivel raceway construction for extra strength.
Hardened Raceways.
Zerk fitting on swivel raceway for lubrication.
Corrosion-resistant zinc plated finish.

Applications

Excellent for camera carts, cargo containers & food handling equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C4560S-PNU	C4560R-PNU	6"	2"	Pneumatic	Ball Bearing	7-1/2"	4-7/16"	185
C4580S-PNU	C4580R-PNU	8"	2-1/2"			11"	6-5/8"	350
C4510S-PNU	C4510R-PNU	10"	3-1/2"			13"	8-1/4"	375
C4560S-PFP	C4560R-PFP	6"	2"	Poly Filled Pneumatic	Ball Bearing	7-1/2"	4-7/16"	210
C4580S-PFP	C4580R-PFP	8"	2-1/2"			11"	6-5/8"	400
C4510S-PFP	C4510R-PFP	10"	3-1/2"			13"	8-1/4"	425
FASTENING TYPE		SPECIFICATIONS						
Top Plate		Overall Size			4 X 4-1/2"			
		Bolt Hole Spacing			2-5/8 X 3-5/8 TO 3 X 3"			
		Attaching Bolt Size			3/8"			
Accessories Code								
TB		Top Locking Brake						
SWL		4-Position Swivel Lock						



8705 Tamarack Ave., Sun Valley, Ca. 91352
Toll Free (877) 252-0878---Phone (818) 252-0878---Fax (818) 252-0978