



2006 CATALOG

30 Series Light Duty Casters



Features

High Durability Design.
Double row ball bearing swivel raceway construction.
Corrosion-resistant zinc plated finish.
Raceway and yoke hardened for extra strength.
Top locking brake system.

Applications

Interior furniture, office chairs, show cases etc..

CASTER PART #	WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C3020-**-SR	2"	13/16"	Soft Rubber	Nylon	2-5/8"	1-13/16"	66
C3020-**-HR			Hard Rubber	Nylon			77
C3020-**-PY			Polyurethane	Plain			66
C3020-**-INF			Infinity	Steel			66
C3025-**-SR	2-1/2"	13/16"	Soft Rubber	Nylon	3-1/8"	2-1/16"	77
C3025-**-HR			Hard Rubber	Nylon			99
C3030-**-SR	3"	13/16"	Soft Rubber	Nylon	3-5/8"	2-3/8"	99
C3030-**-HR			Hard Rubber	Nylon			110
C3030-**-PY			Polyurethane	Plain			100
C3030-**-INF			Infinity	Steel			100
FASTENING TYPE	FASTENING CODE			SPECIFICATIONS			
Top Plate	A1			Overall Size	1-1/4 X 2-1/16"		
				Bolt Hole Spacing	13/16 X 1-9/16"		
				Attaching Bolt Size	3/16"		
Grip Ring Stem	12			7/16 X 1-7/16"			
Threaded Stem	24			3/8-16 X 1-1/4"			

Side locking brakes are available, Add "-BRK" to the part number

80 Series

Business Machine Casters



Features

Double row ball bearing swivel raceway construction.
Corrosion-resistant zinc plated finish.
Provides floor protection and excellent mobility
Low profile design.

Applications

Pianos and other heavy equipment.

CASTER PART #	WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C8020S-A2-HP	2"	1-11/16"	Heavy Duty Plastic	Plain	2-13/16"	1-7/8"	400
C8022S-**-SR	2"	13/16" (2 Wheels)	Soft Rubber	Nylon	2-13/16"	1-7/8"	160
C8022S-**-HR			Hard Rubber	Nylon			200
C8030S-A3-PH	3"	1-13/16"	Phenolic	Roller	4-1/16"	2-5/16"	600
C8030S-A3-HP			Heavy Duty Plastic	Plain			600
C8030S-A3-NGF			Nylon Glass-Filled	Roller			600
TYPE	CODE	SPECIFICATIONS			USE WITH PART NUMBERS		
Top plate	A1	Overall	1-7/8 X 2-9/16"		C8022S		
		Hole Spacing	15/16 X 2-1/8"				
		Attaching Bolt Size	1/4"				
Top plate	A2	Overall	2-3/4 X 3-3/4"		C8020S, C8022S		
		Hole Spacing	1-3/4 X 2-7/8"				
		Attaching Bolt Size	5/16"				
Top plate	A3	Overall	3-1/8 X 4-1/8"		C8030S		
		Hole Spacing	2-3/8 X 3-23/64"				
		Attaching Bolt Size	5/16"				
Grip Ring	12	7/16 X 1-1/2"			C8022S		
Threaded Stem	21	1/2-13 X 1-1/2"			C8022S		

**10 Series
General Duty Casters**



Features

Deeply embossed, formed steel top plate & yoke.
Single row ball bearing swivel raceway.
Corrosion-resistant zinc plated finish.
Simple side locking brake system.

Applications

Widely used in factories & warehouses on furniture dollies, platform trucks, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C1020S-**-SR	C1020R-**-SR	2"	15/16"	Soft Rubber	Nylon	2-7/16"	1-3/4"	90
C1020S-**-HR	C1020R-**-HR			Hard Rubber	Nylon			125
C1020S-**-LP	C1020R-**-LP			Plastic	Plain			125
C1020S-**-PU	C1020R-**-PU			Polyurethane	Plain			125
C1020S-**-SS	C1020R-**-SS			Steel	Plain			125
C1025S-**-SR	C1025R-**-SR	2-1/2"	1-1/8"	Soft Rubber	Nylon	3-1/4"	2-3/8"	100
C1025S-**-HR	C1025R-**-HR			Hard Rubber	Nylon			200
C1025S-**-LP	C1025R-**-LP			Plastic	Plain			175
C1025S-**-PU	C1025R-**-PU			Polyurethane	Plain			140
C1025S-**-SS	C1025R-**-SS			Steel	Plain			200
C1030S-**-SR	C1030R-**-SR	3"	1-1/4"	Soft Rubber	Nylon	3-13/16"	2-7/16"	125
C1030S-**-HR	C1030R-**-HR			Hard Rubber	Nylon			250
C1030S-**-LP	C1030R-**-LP			Plastic	Plain			220
C1030S-**-PU	C1030R-**-PU			Polyurethane	Plain			220
C1030S-**-SS	C1030R-**-SS			Steel	Plain			250
C-1040S-**-SR	C-1040R-**-SR	4"	1-1/4"	Soft Rubber	Nylon	5"	3-1/4"	200
C1040S-**-HR	C1040R-**-HR			Hard Rubber	Nylon			300
C1040S-**-HP	C1040R-**-HP			Heavy Plastic	Plain			300
C1040S-**-SS	C1040R-**-SS			Steel	Plain			300

Caster Part Number	Wheel Size	Fastening Type	Overall Size	Bolt Hole Spacing	Attaching Bolt Size
C1020S	2"	Top Plate	1-7/8 X 2-9/16"	15/16 X 2-1/8"	1/4"
C1025S	2-1/2"		2-3/4 X 3-27/32"	1-3/4 X 3"	5/16"
C1030S	3"		3-1/8 X 4-1/16"	2-3/8 X 3-11/32 to 3-7/16"	5/16"
C1040S	4"		4 X 5-1/8"	3 X 4	3/8"
C1020R	2"	Top Plate	1-1/2 X 2-21/32"	15/16 X 2-1/8"	1/4"
C1025R	2-1/2"		2-1/4 X 4-7/16"	1-1/16 X 3-1/2"	5/16"
C1030R	3"		2-1/2 X 4-7/8"	1-3/16 X 3-7/8 to 4"	5/16"
C1040R	4"		2-3/4 X 6	1-3/4 X 4-15/16 to 5	3/8"

**20 Series
Light Medium Duty Casters**



Features

Heavily embossed, formed steel upper & lower cup.
Double row ball bearing swivel raceway construction.
Corrosion-resistant zinc plated finish.
Top locking brake system.

Applications

Stock carts, bakery racks, food service equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C2030S-**-SR	C2030R-**-SR	3"	1-1/4"	Soft Rubber	Nylon	4-1/4"	3"	125
C2030S-**-SRB	C2030R-**-SRB			Soft Rubber	Ball			125
C2030S-**-HR	C2030R-**-HR			Hard Rubber	Nylon			250
C2030S-**-HRB	C2030R-**-HRB			Hard Rubber	Ball			250
C2030S-**-HP	C2030R-**-HP			Heavy Plastic	Plain			250
C2030S-**-PY	C2030R-**-PY			Polyurethane	Ball			220
C2030S-**-INF	C2030R-**-INF			Infinity	Annular			220
C2030S-**-SS	C2030R-**-SS			Steel	Plain			250
C2035S-**-SR	C2035R-**-SR			3-1/2"	1-1/4"			Soft Rubber
C2035S-**-HR	C2035R-**-HR	Hard Rubber	Nylon			255		
C2035S-**-HP	C2035R-**-HP	Heavy Plastic	Nylon			255		
C2035S-**-PY	C2035R-**-PY	Polyurethane	Ball			260		
C2035S-**-INF	C2035R-**-INF	Infinity	Annular			220		
C2035S-**-RAL	C2035R-**-RAL	Rubber/Aluminum	Annular			220		
C2040S-**-SR	C2040R-**-SR	4"	1-1/4"	Soft Rubber	Nylon	5-1/8"	3-1/2"	165
C2040S-**-SRB	C2040R-**-SRB			Soft Rubber	Ball			165
C2040S-**-HR	C2040R-**-HR			Hard Rubber	Nylon			255
C2040S-**-HRB	C2040R-**-HRB			Hard Rubber	Ball			255
C2040S-**-HP	C2040R-**-HP			Plastic	Plain			265
C2040S-**-PY	C2040R-**-PY			Polyurethane	Ball			265
C2040S-**-INF	C2040R-**-INF			Infinity	Annular			240
C2040S-**-SS	C2040R-**-SS			Steel	Plain			300
C2040S-**-HT	C2040R-**-HT			High Temp	Steel			265
C2050S-**-SR	C2050R-**-SR	5"	1-1/4"	Soft Rubber	Nylon	6-5/32"	4	175
C2050S-**-SRB	C2050R-**-SRB			Soft Rubber	Ball			175
C2050S-**-HR	C2050R-**-HR			Hard Rubber	Nylon			260
C2050S-**-HRB	C2050R-**-HRB			Hard Rubber	Ball			260
C2050S-**-HP	C2050R-**-HP			Plastic	Plain			300
C2050S-**-PY	C2050R-**-PY			Polyurethane	Ball			250
C2050S-**-INF	C2050R-**-INF			Infinity	Annular			250
C2050S-**-PH	C2050R-**-PH			Phenolic	Steel			300
FASTENING TYPE		FASTENING CODE			SPECIFICATIONS			
Top Plate		A1	Overall Size		2-3/8 X 3-5/8"			
			Bolt Hole Spacing		1-3/4 X 2-11/16 to 2-15/16"			
			Attaching Bolt Size		5-16"			
Threaded Stem		A2	Overall Size		3-1/8 X 4-1/8"			
			Bolt Hole Spacing		1-3/4 X 2-15/16 to 2-3/8 X 3-3/8"			
			Attaching Bolt Size		3/8"			
Grip Ring Stem		A3	Overall Size		3-15/16 X 4-1/2"			
			Bolt Hole Spacing		2-5/8 X 3 to 3-5/8"			
			Attaching Bolt Size		3/8"			
			Bolt Hole Spacing		2-5/8 X 3 to 3-5/8"			
Threaded Stem		B1	1/2-13 X 1					
		B2	1/2-13 X 1-1/2"					
		B3	1/2-13 X 2-1/2" (Can be used with expanding applicator)					
		B4	5/8-11 X 1-1/4"					
Grip Ring Stem		D1	7/16 X 1-1/2"					
Octagon Stem		F1	27/32 X 2-7/16" with 1/4" cross drilled holes located 1/2, 1-1/8 & 1-3/4" from the top of raceway					
Accessories Code								
TB		Top Lock Brake						
TG		Thread Guard (Only on Casters with HRB & SRB wheels)						
STS		Stainless Steel Yoke						

**21 Series
Light Medium Duty Casters**



Features

Heavily embossed, formed steel upper & lower cup.
 Double row ball bearing swivel raceway construction.
 Dust cover helps protect swivel bearings.
 Corrosion-resistant zinc plated finish
 Top locking brake system.

Applications

Stock carts, bakery racks, food service equipment, sound & music equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C2125S-**-SR	C2125R-**-SR	2-1/2"	1-1/4"	Soft Rubber	Nylon	3-5/8"	2-3/4"	140
C2125S-**-HR	C2125R-**-HR			Hard Rubber	Nylon			210
C2125S-**-HP	C2125R-**-HP			Heavy Plastic	Plain			210
C2125S-**-PY	C2125R-**-PY			Polyurethane	Ball			210
C2130S-**-SR	C2130R-**-SR	3"	1-1/4"	Soft Rubber	Nylon	4-1/4"	2-3/4"	125
C2130S-**-SRB	C2130R-**-SRB			Soft Rubber	Ball			125
C2130S-**-HR	C2130R-**-HR			Hard Rubber	Nylon			250
C2130S-**-HRB	C2130R-**-HRB			Hard Rubber	Ball			250
C2130S-**-HP	C2130R-**-HP			Heavy Plastic	Plain			250
C2130S-**-PY	C2130R-**-PY			Polyurethane	Ball			220
C2130S-**-INF	C2130R-**-INF			Infinity	Annular			220
C2130S-**-SS	C2130R-**-SS			Steel	Plain			250
C2135S-**-SR	C2135R-**-SR	3-1/2"	1-1/4"	Soft Rubber	Nylon	4-11/16"	3-1/16"	130
C2135S-**-HR	C2135R-**-HR			Hard Rubber	Nylon			255
C2135S-**-HP	C2135R-**-HP			Heavy Plastic	Plain			255
C2135S-**-PY	C2135R-**-PY			Polyurethane	Ball			260
C2135S-**-INF	C2135R-**-INF			Infinity	Annular			230
C2135S-**-RAL	C2135R-**-RAL			Rubber/Aluminum	Annular			220
C2140S-**-SR	C2140R-**-SR	4"	1-1/4"	Soft Rubber	Nylon	5-1/8"	3-5/16"	165
C2140S-**-SRB	C2140R-**-SRB			Soft Rubber	Ball			165
C2140S-**-HR	C2140R-**-HR			Hard Rubber	Nylon			255
C2140S-**-HRB	C2140R-**-HRB			Hard Rubber	Ball			255
C2140S-**-HP	C2140R-**-HP			Heavy Plastic	Plain			265
C2140S-**-PY	C2140R-**-PY			Polyurethane	Ball			265
C2140S-**-INF	C2140R-**-INF			Infinity	Annular			250
C2140S-**-SS	C2140R-**-SS			Steel	Plain			300
C2140S-**-HT	C2140R-**-HT			High Temp	Plain			265
C2150S-**-SR	C2150R-**-SR	5"	1-1/4"	Soft Rubber	Nylon	6-7/32"	4"	175
C2150S-**-SRB	C2150R-**-SRB			Soft Rubber	Ball			175
C2150S-**-HR	C2150R-**-HR			Hard Rubber	Nylon			260
C2150S-**-HRB	C2150R-**-HRB			Hard Rubber	Ball			260
C2150S-**-HP	C2150R-**-HP			Heavy Plastic	Plain			300
C2150S-**-PY	C2150R-**-PY			Polyurethane	Ball			250
C2150S-**-INF	C2150R-**-INF			Infinity	Annular			250
C2150S-**-PH	C2150R-**-PH			Phenolic	Steel			300

FASTENING TYPE	FASTENING CODE	SPECIFICATIONS	
Top Plate	A1	Overall Size	2-3/8 X 3-5/8"
		Bolt Hole Spacing	1-3/4 X 2-11/16 to 2-15/16"
		Attaching Bolt Size	5-16"
	A2	Overall Size	3-1/8 X 4-1/8"
		Bolt Hole Spacing	1-3/4 X 2-15/16 to 2-3/8 X 3-3/8"
		Attaching Bolt Size	3/8"
	A3	Overall Size	3-15/16 X 4-1/2"
		Bolt Hole Spacing	2-5/8 X 3 to 3 X 3-5/8"
		Attaching Bolt Size	3/8"
Threaded Stem	B2	1/2-13 X 1-1/2"	
	B3	1/2-13 X 2-1/2" (Can be used with expanding applicator)	
Accessories Code			
TB	Top Lock Brake		
TG	Thread Guard (Only on Casters with HRB & SRB wheels)		
TLB	Total Lock Brake (Locks the swivel raceway and the wheel) Only available in 3-1/2, 4 or 5"		

**40 Series
Medium Heavy Duty Casters**



Features

Cold forged top plate & base.
 Double row ball bearing swivel raceway construction.
 Hardened Raceways.
 Zerk fitting on swivel raceway for lubrication.
 Legs are formed and welded to yoke base for strength.

Applications

Excellent for medium heavy duty platform carts, food service equipment and large stock carts, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C4040S-**-RC	C4040R-**-RC	4	2	Rubber/Cast Iron	Roller	5-5/8"	3-3/16"	350
C4040S-**-PC	C4040R-**-PC			Poly/Cast Iron				700
C4040S-**-PU	C4040R-**-PU			Poly/Polyolefin				500
C4040S-**-HP	C4040R-**-HP			Heavy Plastic				500
C4040S-**-PH	C4040R-**-PH			Phenolic				700
C4040S-**-SS	C4040R-**-SS			Cast Iron				700
C4040S-**-VG	C4040R-**-VG			V-Groove				700
C4040S-**-TR	C4040R-**-TR			Thermal Rubber				350
C4050S-**-RC	C4050R-**-RC			5				2
C4050S-**-PC	C4050R-**-PC	Poly/Cast Iron	800					
C4050S-**-PU	C4050R-**-PU	Poly/Polyolefin	800					
C4050S-**-HP	C4050R-**-HP	Heavy Plastic	650					
C4050S-**-PH	C4050R-**-PH	Phenolic	800					
C4050S-**-SS	C4050R-**-SS	Cast Iron	800					
C4050S-**-VG	C4050R-**-VG	V-Groove	800					
C4050S-**-TR	C4050R-**-TR	Thermal Rubber	375					
C4060S-**-RC	C4060R-**-RC	6	2		Rubber/Cast Iron	Roller	7-1/2"	
C4060S-**-PC	C4060R-**-PC			Poly/Cast Iron	800			
C4060S-**-PU	C4060R-**-PU			Poly/Polyolefin	800			
C4060S-**-HP	C4060R-**-HP			Heavy Plastic	700			
C4060S-**-PH	C4060R-**-PH			Phenolic	800			
C4060S-**-SS	C4060R-**-SS			Cast Iron	800			
C4060S-**-VG	C4060R-**-VG			V-Groove	800			
C4060S-**-TR	C4060R-**-TR			Thermal Rubber	450			
C4080S-**-RC	C4080R-**-RC			8	2			Rubber/Cast Iron
C4080S-**-PC	C4080R-**-PC	Poly/Cast Iron	900					
C4080S-**-PU	C4080R-**-PU	Poly/Polyolefin	900					
C4080S-**-HP	C4080R-**-HP	Heavy Plastic	800					
C4080S-**-PH	C4080R-**-PH	Phenolic	900					
C4080S-**-SS	C4080R-**-SS	Cast Iron	900					
C4080S-**-VG	C4080R-**-VG	V-Groove	900					
C4080S-**-TR	C4080R-**-TR	Thermal Rubber	500					

FASTENING TYPE		SPECIFICATIONS	
Top Plate	A1	Overall Size	4 X 4-1/2"
		Bolt Hole Spacing	2-5/8 X 3-5/8 TO 3 X 3"
		Attaching Bolt Size	3/8"
	A2	Overall Size	4-1/2 X 6-1/4"
Bolt Hole Spacing		2-7/16 X 4-15/16 to 3-3/8 X 5-1/4"	
Attaching Bolt Size		1/2"	
Accessories Code			
	TB	Top Locking Brake	
	SWL	4-Position Swivel Lock	
	ZA	Zerk Axle	
	STS	Stainless Steel	

42 Series Heavy Duty Casters



Features

Cold Forged top plate and base.
Double row ball bearing swivel raceway construction for extra strength.
Corrosion-resistant zinc plated finish.
Raceway and yoke hardened for extra strength.
3/4" Diameter king pin.

Applications

Excellent for cargo containers, heavy duty platform trucks, food handling equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C4260S-A1-RC	C4260R-A1-RC	6"	2-1/2"	Rubber-Cast Iron	Roller	7-1/2"	4-7/16"	500
C4260S-A1-PC	C4260R-A1-PC			Ploy-Cast Iron				1500
C4260S-A1-PH	C4260R-A1-PH			Phenolic				1500
C4260S-A1-SS	C4260R-A1-SS			Steel				1500
C4280S-A1-RC	C4280R-A1-RC	8"	2-1/2"	Rubber-Cast Iron	Roller	9-1/2"	6"	600
C4280S-A1-PC	C4280R-A1-PC			Poly-Cast Iron				1600
C4280S-A1-PH	C4280R-A1-PH			Phenolic				1600
C4280S-A1-SS	C4280R-A1-SS			Steel				1600
C4210S-A1-RC	C4210R-A1-RC	10"	2-1/2"	Rubber-Cast Iron	Roller	11-1/2"	7-19/32"	800
C4210S-A1-PC	C4210R-A1-PC			Poly-Cast Iron				2200
C4210S-A1-PH	C4210R-A1-PH			Phenolic				2200
C4210S-A1-SS	C4210R-A1-SS			Steel				2200
FASTENING TYPE		SPECIFICATIONS						
Top Plate		Overall Size			4-1/2 X 6-1/4"			
		Bolt Hole Spacing			2-7/16 X 4-15/16 to 3-3/8 X 5-1/4"			
		Attaching Bolt Size			1/2"			

45 Series Pneumatic Casters



Features

Cold Forged top plate and base.
Double row ball bearing swivel raceway construction for extra strength.
Hardened Raceways.
Zerk fitting on swivel raceway for lubrication.
Corrosion-resistant zinc plated finish.

Applications

Excellent for camera carts, cargo containers & food handling equipment, etc..

CASTER PART #		WHEEL SPECIFICATIONS				CASTER SPECIFICATIONS		
Swivel	Rigid	Diameter	Tread Width	Wheel Type	Bearing	Overall Height	Swivel Radius	Load Capacity
C4560S-PNU	C4560R-PNU	6"	2"	Pneumatic	Ball Bearing	7-1/2"	4-7/16"	185
C4580S-PNU	C4580R-PNU	8"	2-1/2"			11"	6-5/8"	350
C4510S-PNU	C4510R-PNU	10"	3-1/2"			13"	8-1/4"	375
C4560S-PFP	C4560R-PFP	6"	2"	Poly Filled Pneumatic	Ball Bearing	7-1/2"	4-7/16"	210
C4580S-PFP	C4580R-PFP	8"	2-1/2"			11"	6-5/8"	400
C4510S-PFP	C4510R-PFP	10"	3-1/2"			13"	8-1/4"	425
FASTENING TYPE		SPECIFICATIONS						
Top Plate		Overall Size			4 X 4-1/2"			
		Bolt Hole Spacing			2-5/8 X 3-5/8 TO 3 X 3"			
		Attaching Bolt Size			3/8"			
Accessories Code								
TB		Top Locking Brake						
SWL		4-Position Swivel Lock						



8705 Tamarack Ave., Sun Valley, Ca. 91352
Toll Free (877) 252-0878---Phone (818) 252-0878---Fax (818) 252-0978